



# CFPT-140-MVRR


3 WAYS FLOW REGULATOR  
ADJUSTABLE SETTING



Dimensions: mm [inches]



3 way application



2 way application,  
port 2 not connected


## SPECIFICATIONS

Max. operating pressure:	350 bar (5000 psi)
Rated flow:	140 l/min (37 gpm)
Cavity:	SAE-16-3N
Weight:	0,7 kg (1,54 lbs)
Seal kit:	RB700094
Installation torque:	118 - 132 Nm (160 - 179 ft-lb)
Contamination class to ISO 4406:	See technical spec.
MTTFa:	150 years

## NOTES


If port 2 is blocked the valve operates as a two way flow regulator.  
Port 2 can be pressurized.

## OPTIONS





Graduated handknob  
for flow regulation  
under pressure

The washer is used  
to indicate the zero.



Ordering code:  
SV000083

## CURVES



## ORDERING CODES

Quick code	Description	Regulated flow range	Adjustment option
CF000310	CFPT-140-MVRR-15-S16-N350	0-15 l/min (0-4 gpm)	Graduated handknob
CF000311	CFPT-140-MVRR-25-S16-N350	0-25 l/min (0-7 gpm)	Graduated handknob
CF000312	CFPT-140-MVRR-35-S16-N350	0-35 l/min (0-9 gpm)	Graduated handknob
CF000313	CFPT-140-MVRR-50-S16-N350	0-50 l/min (0-13 gpm)	Graduated handknob
CF000314	CFPT-140-MVRR-65-S16-N350	0-65 l/min (0-17 gpm)	Graduated handknob
CF000315	CFPT-140-MVRR-80-S16-N350	0-80 l/min (0-21 gpm)	Graduated handknob