



General tolerances : 0.03 mm

⊙	0.03
⊥	0.02

	SAE-08-3C	SAE-10-3C	SAE-12-3C	SAE-16-3C	SAE-20-3C
A	3/4-16 UNF	7/8-14 UNF	1-1/16 12 UNF	1-5/16 12 UNF	1-5/8 12 UNF
B	26	30	35	42	48
C	20.6 ^{+0.1} ₀	23.9 ^{+0.1} ₀	29.2 ^{+0.1} ₀	35.5 ^{+0.1} ₀	43.5 ^{+0.1} ₀
D1	15.87 ^{+0.05} ₀	19.05 ^{+0.05} ₀	23.80 ^{+0.05} ₀	28.6 ^{+0.05} ₀	36.52 ^{+0.05} ₀
D2	14.27 ^{+0.05} ₀	17.47 ^{+0.05} ₀	22.22 ^{+0.05} ₀	25.42 ^{+0.05} ₀	33.35 ^{+0.05} ₀
E	2.6 ^{+0.3} ₀	2.6 ^{+0.3} ₀	3.3 ^{+0.3} ₀	3.3 ^{+0.3} ₀	3.4 ^{+0.3} ₀
F	12	13	21	16.5	20
G	8	14	14	15	28
G1	3	4	5	5	7
G2	12	15	19	24	30
H1	12.5	14	22.5	17.5	20
H2	26.5	31.5	40.5	38	50
L1	16	18	26.5	22	25.5
L2	32	40	49.5	47.5	65.5
L3	40	49	60	58	78